

TEROSON VR 320

July 2014

PRODUCT DESCRIPTION

TEROSON VR 320 provides the following characteristics:

Technology	Hand washing paste
Additional Information	Solvent free , based on anionic surfactants

TEROSON VR 320 is a highly-effective washing paste for cleaning heavily soiled hands. It is based on anionic surfactants and contains no solvents. The product does not contain sand therefore will not easily block dispensers. The abrasive used in TEROSON VR 320 is a smooth-edged and gentle softwood sawdust which will not damage the skin (no splinters). TEROSON VR 320 has been classified as easily biodegradable under OECD-302 B (Test NO. 8901AL02542, February 1989, Fresenius Institute, Taunusstein).

Application areas:

TEROSON VR 320 is particularly suitable for the rapid and thorough cleaning of heavily soiled hands in garage workshops.

TECHNICAL DATA

(Typical Test Results)

Colour:	light beige paste
Odour	perfumed
Consistency	paste
Density	approx. 0.82 g/cm ³
pH value	approx. 6.5

Application:

Moisten soiled hands with water, apply TEROSON VR 320 and rub thoroughly (if necessary use the attached hand washing brush). Then rinse thoroughly under running water. If a skin protector (such as Barrier Cream) was used before starting work, this should be removed with clean water or an alkaline cleaner (e.g. soap) prior to washing with TEROSON VR 320.

Storage:

Frost sensitive	yes
Recommended storage temperature	5 to 25 °C
Shelf life	12 months

Disclaimer

Note:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage: [Except as otherwise noted] All trademarks in this document are trademarks and/or registered trademarks of Henkel and its affiliates in the U.S. and elsewhere.

Henkel AG & Co. KGaA

D-40191 Düsseldorf, Germany

Phone: +49-211-797-0

www.henkel.com

Henkel Central Eastern Europe GmbH

A-1030 Wien, Austria

Phone: +43-1711-040

www.henkel.com

Henkel & Cie AG

CH-4133 Pratteln, Switzerland

Phone: +41-61-825-7000

www.henkel.com

